



HEAD OFFICE
22 Park Drive
Dandenong VIC 3175
Phone: (03) 9768 4900
Fax (03) 9768 4999

NSW OFFICE
14 Artisan Road
Seven Hills NSW 2147
Phone: (02) 9838 4868
Fax (02) 9838 9555

www.unitex.com.au

MATERIAL SAFETY DATA SHEET (MSDS)

PRODUCT: BASEBOARD RENDER

DATE OF ISSUE: OCTOBER 2007

1. PRODUCT INFORMATION

Product Name:	BASEBOARD RENDER
Uses:	Internal and external rendering
UN Number:	Not Applicable
Dangerous Goods Class:	Not Applicable
Hazchem Code:	Not Applicable
Poisons Code:	Not Applicable

2. PHYSICAL DATA

Appearance:	An off white mixture containing finely ground materials (Portland cement, Fly Ash and Hydrated Lime) and sand up to 2mm in size. 1.6mm in size
Boiling Point/ Melting Point (°C):	Not Applicable
Vapour Pressure:	Not Applicable
% Volatiles:	Not Applicable
Specific Gravity:	Average S.G. approximately 2.5
Bulk Density:	1550 – 1750
Auto Ignition Temperature:	Not Applicable
Other Properties:	Not Explosive, no odour, hardens on reaction with water. Slightly soluble in water.
Flash Point:	Not Applicable
Flammability Limits:	Not Applicable
Special Fire Fighting:	Not Applicable

3. CHEMICAL DATA

The product contains washed sand and approximately 25% (wt) of binder which is a mixture of Portland cement, Hydrate Lime, Fly Ash, and organics. The principal oxides are present in the binder in the following concentrations:-

<u>Binder Composition</u>	<u>Percentage by Weight</u> (in Binder Only)
CAO	60 – 70
SiO ₂	20 – 25
Al ₂ O ₃	6 – 10
FE ₂ O ₃	1 – 5

These materials are present as Calcium, Silica and aluminium

Other oxides present include SO₃ (as gypsum or alkali Sulphate) and small traces of MgO, Na₂O, K₂O, TiO₂ and P₂O₅. Hexavalent chromium may be present in concentration.

Sand is essentially silica with low clay content.

Trace quantities (less than 3.0%) of methyl cellulose, starch ether, and redispersible additives are used to give improved working and adhesive properties.

4. FIRE AND EXPLOSION HAZARD DATA

Flash Point	Not Applicable
Flammability Limits:	Not Applicable
Extinguishing Media:	Not Applicable
Special Fire Fighting:	Not Applicable
Unusual & Explosion Hazards:	Not Applicable

BASEBOARD RENDER is a stable, non-combustible material which does not decompose into hazardous by-products



5. HEALTH HAZARD DATA

5.1 Health Effects

BASEBOARD RENDER contains trace amounts of respirable quartz sand, and care must be taken to avoid excessive amounts of dust.

Short Term Exposure

The Portland Cement content of BASEBOARD RENDER is classified as an inert nuisance dust only. Exposure can irritate skin, eyes and mucous membranes.

Long Term Exposure

Wet Portland Cement, especially as an ingredient in plastic (unhardened) concrete, mortar or slurry, is slightly caustic and can dry the skin, and cause alkali burns. There may also be trace amounts of water soluble hexavalent chromium present in Portland Cement which may cause allergic dermatitis in some individuals. In dust form Portland Cement may cause inflammation of lining tissue of the respiratory system and inflammation of the cornea.

5.2 First Aid

Skin:	Wash with tepid soapy water.
Eyes:	Flush with cool water for at least 10 minutes and seek medical attention.
Swallowed:	Wash mouth and lips with water and seek medical attention.
Inhaled:	Move to fresh air, wash with water and seek medical attention if effects persist.

6. PRECAUTIONS OF USE

6.1 Exposure Limits

Wet Portland Cement, particularly in plastic (unhardened) concrete, mortar or slurry, can dry the skin and cause alkali burns. Continued exposure to individuals who are allergic to chromium, could cause severe allergic dermatitis.

6.2 Ventilation

Where practical, suitable means of dust collection/suppression should be applied as necessary to maintain acceptable air borne dust levels. Persons with a history of respiratory illness or reduced pulmonary function should avoid work places with high dust levels.

6.3 Personal Protection

In dusty environments, the use of filter masks as in AS1716 (Class A) and tight fitting goggles is advised. Use of barrier creams or impervious gloves, boots and clothing to protect the skin from contact with dust and wet Portland Cement mortar is recommended.

6.4 Flammability

BASEBOARD RENDER is non combustible



7. PRECAUTIONS FOR USE

7.1 Exposure Limits

Wet Portland Cement, particularly in plastic (unhardened) concretes, mortar or slurry, can dry the skin and cause alkali burns. In rare instances continued exposure to cement, by individuals who are allergic to chromium, could cause allergic dermatitis.

7.2 TLU (Threshold Limit Value)

5mg/m³ for total dust. Limit applies to an adult exposed for an 8 hour period, with no adverse effects.

7.3 Ventilation

Where practical, suitable means of dust collection/suppression should be applied as necessary to maintain acceptable air borne dust levels.

Persons with a history of respiratory illness or reduced pulmonary function should avoid work in places with high dust levels.

7.4 Personal Protection

In dusty environments, the use of filter masks as in AS1716 (Class L) and tight fitting goggles are advised. Use of barrier creams and impervious gloves, boots and clothing to protect the skin from contact with dust and wet Portland Cement mortar is recommended.

Following work with BASEBOARD RENDER, normal hygiene procedures should apply

7.5 Flammability

BASEBOARD RENDER is non combustible

8. SAFE HANDLING INFORMATION

8.1 Handling and Storage

BASEBOARD RENDER should be stored in a dry place, in the original places lined pails.

Drivers of trucks transporting BASEBOARD RENDER should ensure that the pails are correctly restrained on a pallet. BASEBOARD RENDER is supplied in 19kg bags and recognised local safe lifting methods should be used.

8.2 Spills and Disposal

Spillages should be cleaned up with a broom, shovel or suitable vacuum equipment by suitably attired personnel

9. CONTACT POINT

Telephone: 03 9768 4900
Ask For: Operations Manager

This information contained herein relates only to the specific material identified. Unitex Granular Marble Pty Ltd believes that such information is accurate and reliable as of the date of this material safety data sheet, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability or completeness of the information.

Unitex urges persons receiving this information to make their own determination as to the information's suitability and completeness for their particular application.