

Phone: (03) 9768 4900 Fax (03) 9768 4999 Unitex (NSW)
14 Artisan Road
Seven Hills NSW 2147

Phone: **(02) 9838 0911** Fax **(02) 9838 9555 www.unitex.com.au**

URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

Phone: 1800 RENDER Phones Fax (03) 9544 3620 Fax www.render.com.au www

URW (SA) 20 Cardiff Court Cavan SA 5094

Phone: (08) 8262 7900 Fax (08) 8262 7922 www.render.com.au

Material Safety Data Sheet

PRODUCT: Unitex® Uni-Dry Cote® Redi Render

DATE OF ISSUE: 24th July 2015

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Information

Trade name: Unitex® Uni-Dry® Cote Redi Render

Company Unitex Granular Marble Pty Ltd

22 Park Drive

Dandenong, Vic. 3175

Australia

Telephone +61 3 9768 4900 Telefax +61 3 9768 4999

Emergency telephone

Number

+61 3 9768 4900 (BH)

Use of the Product render for coating over masonry

2. HAZARDS IDENTIFICATION

THIS PRODUCT IS CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF NOHSC

The product contains Portland cement, inorganic extender pigments and organic functional additives. Portland cement is classified as a Hazardous Substance, Non-Dangerous Goods according to the criteria of NOHSC. All other components are classified as Non Hazardous, Non Dangerous Goods.

Risk phrases for Portland cement are:

R36/37/38 Irritating to eyes, respiratory system and skin

R40 Possible risk of irreversible effects R43 May cause sensitization by skin contact

R48/20 Harmful: danger of serious damage to health by prolonged exposure through

inhalation

Safety Phrases for Portland cement

S22 Do not breathe dust

S24/25 Avoid contact with skin and eyes

S36/37 Wear suitable protective clothing and gloves



Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au Unitex (NSW)
14 Artisan Road
Seven Hills NSW 2147

Phone: **(02) 9838 0911** Fax **(02) 9838 9555** www.unitex.com.au

URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

Phone: 1800 RENDER
Fax (03) 9544 3620
www.render.com.au

20 Cardiff Court Cavan SA 5094

URW (SA)

Phone: (08) 8262 7900 Fax (08) 8262 7922 www.render.com.au

The chemical composition of the product is essentially oxides of various elements, the most prevalent being oxides of calcium Ca, silica Si, aluminium AI, iron Fe, titanium Ti, chromium Cr (mostly as insoluble Cr III but it is possible that water soluble Cr IV could be present at concentrations of less than 10 ppm). Trace amounts of oxides of magnesium Mg, potassium K and phosphorus P may also be present. As cement is a blended product, crystalline silica at levels less than 0.1 % may be present.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Ingredients | CAS Number | Proportion |
|------------------------------|-------------|------------|
| Portland cement | 65997-15-1 | 15-30 % |
| Pigments | proprietary | 5-12 % |
| Inorganic additives | proprietary | 60-75 % |
| Functional organic additives | proprietary | < 2 % |

4. FIRST AID MEASURES

4.1 Health Effects

Swallowed

Health effects Is mildly abrasive and corrosive and may cause nausea/stomach cramps/constipation. Unlikely under normal conditions of use.

First Aid: Rinse mouth with milk or water. DO NOT give carbonated (fizzy) drinks. DO NOT induce vomiting. After rinsing the mouth, give plenty of water to drink. If symptoms persist, seek medical attention.

Eyes

Health effects Irritating and corrosive to the eyes. May cause chemical conjunctivitis, redness, watering and damage to the cornea.

First Aid: Flush eyes with tepid running water for at least 15 minutes, removing any foreign bodies. Seek medical attention if symptoms persist.

Skin Health effects: Irritating and drying to skin – can result in irritant dermatitis from mechanical abrasion. Wet mortar is irritating and corrosive to skin and may cause skin sensitization (dermatitis). There may be a trace of hexavalent chromium present in Portland cement which may cause allergic dermatitis in some individuals.

First Aid Wash with tepid soapy water; shower if necessary.

Inhaled

Health effects: Irritating to the nose, throat and respiratory tract causing coughing and sneezing. Repeated inhalation of the dust may cause bronchitis.

First Aid: Remove to fresh air. Keep at rest. Seek medical advice if symptoms persist.

4.2 Chronic Health Effects

Repeated inhalation of dust may cause bronchitis. It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs).

Advice to Doctor

Treat symptomatically.

Aggravated Medical Conditions Caused by Exposure

Studies have shown that smoking increases the risk of bronchitis. It is recommended that all storage and work areas should be smoke free zones.



Unitex 22 Park Drive

Dandenong VIC 3175

Phone: **(03) 9768 4900** Fax **(03) 9768 4999** www.unitex.com.au

Unitex (NSW)
14 Artisan Road
Seven Hills NSW 2147

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

Phone: 1800 RENDER
Fax (03) 9544 3620
www.render.com.au

URW (SA) 20 Cardiff Court Cavan SA 5094

Phone: (08) 8262 7900 Fax (08) 8262 7922 www.render.com.au

5. FIRE-FIGHTING MEASURES

Hazchem Code None allocated

Flammability Not flammable

Extinguishing media None required

Hazards from combustion

products

None - does not decompose on heating

Special Protective Precautions & Equipment for Fire Fighters

None

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Avoid generating and breathing dust. If dust is generated, wear a class P1 or P2 particulate respirator (AS/NZS 1715, 1716).

Containment Procedures

A fine water spray should be used to suppress dust when sweeping.

Clean-up Procedures

Work areas should be cleaned regularly by wet sweeping or vacuuming. If dust generation cannot be avoided, follow PERSONAL PROTECTION recommendations.

7. HANDLING AND STORAGE

Safe Handling Advice

Provide good ventilation or extraction.

Wear personal protective equipment

Unitex® Uni-Dry Cote® Redi Render is packed in 20 kg multi-ply paper sacks. It is recommended that all manual handling of products greater than 15 kg be undertaken by load shifting equipment. Manual handling of this product is not recommended as this may result in personal injury. If no mechanical aids are available, a sack may be lifted and carried by 2 persons and that each has been trained in how to share the sack weight and move this type of sack.

Advice on protection against fire and explosion

No special protective measures against fire required.

Conditions for Safe Storage

Unitex® Uni-Dry Cote® Redi Render should be stored in a dry place, in their original multi-ply paper sacks. Avoid moisture to prevent hardening. When stored correctly in dry, unopened sacks, a shelf life of 6 months ought to be expected.

Drivers of trucks transporting Unitex® Uni-Dry Cote® Redi Render should ensure that the paper sacks are correctly restrained on a pallet.

Incompatibilities None



Phone: **(03) 9768 4900** Fax **(03) 9768 4999** www.unitex.com.au

14 Artisan Road Seven Hills NSW 2147

Unitex (NSW)

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

Phone: 1800 RENDER
Fax (03) 9544 3620
www.render.com.au

URW (SA) 20 Cardiff Court Cavan SA 5094

Phone: (08) 8262 7900 Fax (08) 8262 7922 www.render.com.au

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure Limits

Unitex® Uni-Dry Cote® Redi Render is supplied as a blended dry powder. Prior to application, the powder is mixed with water and mixed to a smooth, viscous slurry and is then trowel or spray applied onto masonry surfaces such as brick walls. As Unitex® Uni-Dry Cote® Redi Render contains Portland cement as a major component, it is classed as a Hazardous, Non-Dangerous product.

When wet, Unitex® Uni-Dry Cote® Redi Render, particularly in slurry form, can dry the skin and cause alkali burns. Continued exposure to individuals who are allergic to chromium, could cause severe allergic dermatitis.

For powder Portland cement, keep exposure to dust as low as possible. If inspirable dust levels are kept below 2 mg/m³, health problems such as skin, eye and respiratory irritation will be minimised.

8.2 Engineering Controls

Avoid generating dust. All work with Unitex® Uni-Dry Cote® Redi Render should be carried out in such a way as to minimize exposure to dust and repeated skin contact. Where dust could be generated whilst handling the product, use local mechanical ventilation or extraction in areas where dust could escape into the work environment.

Work areas should be cleaned regularly by wet sweeping or vacuuming. If generating dust cannot be avoided, see personal protection recommendations below.

8.3 Ventilation

Where practical, the workplace should be well ventilated with suitable means of dust collection/suppression equipment so as to maintain acceptable airborne dust levels. Persons with a history of respiratory illness or reduced pulmonary function should avoid work places with high dust levels.

8.4 Personal Protection

Skin

Wear loose comfortable protective clothing and impervious boots. Apply barrier creams to hands or wear cotton or light duty leather gloves (AS/NZS 2161). Wash thoroughly after handling. Wash clothes regularly and keep separate from other clothes.

Eyes

Safety spectacles with side shields or safety goggles (dust resistant AS/NZS 1336) should be worn if dust is likely to be generated.

Respiratory

If dust is generated, wear a class P1 or P2 particulate respirator (AS/NZS 1715). Use only respirators which bear the Australian Standards mark and are fitted correctly. Note that persons with facial hair will have difficulty in obtaining a satisfactory face seal. For alternatives, see AS/NZS 1715: Selection and maintenance of Respiratory Protective Devices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Blended powder – grey in shade

Odour None

pH alkaline slurry formed with water



Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au Unitex (NSW)
14 Artisan Road
Seven Hills NSW 2147

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au URW (Oakleigh)
1346 North Road
Oakleigh VIC 3167

Phone: 1800 RENDER Phone: (08) 8262 7900
Fax (03) 9544 3620 Fax (08) 8262 7922
www.render.com.au www.render.com.au

URW (SA)

20 Cardiff Court

Cavan SA 5094

Density approx $2.3 - 2.8 \text{ g/cm}^3$

Boiling point not applicable

Freezing/Melting point > 1400 °C

Vapour density not applicable

Vapour pressure not applicable

Solubility Essentially insoluble. However, some components are slightly soluble in water forming an

alkaline (caustic) product

Flash point not applicable

Ignition temperature not applicable

Additional Information Respirable Fraction: approximately 5-10 % of particles are below 7 microns in diameter (in

the respirable range)

10. STABILITY AND REACTIVITY

Chemical Stability Chemically stable

Conditions to avoid Keep in moisture proof containers to prevent hardening

Incompatible Materials Will harden in moist conditions

Hazardous Decomposition

Products

None

Hazardous Reactions Avoid reaction with hydrogen fluoride (hydrofluoric acid) and other fluorine containing

compounds

11. TOXICOLOGICAL INFORMATION

Health effects from the likely

routes of exposure

Refer Section 4: FIRST AID MEASURES

12. ECOLOGICAL INFORMATION

Ecotoxicity No information available. Product may be eco-damaging as it can form an alkaline slurry

with water.

Persistence & Degradability Product would be persistent and have a low degradability.



Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au Unitex (NSW)
14 Artisan Road
Seven Hills NSW 2147

Phone: **(02) 9838 0911** Fax **(02) 9838 9555 www.unitex.com.au**

URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

Phone: 1800 RENDER Phone: (08) 8262 7900
Fax (03) 9544 3620 Fax (08) 8262 7922
www.render.com.au www.render.com.au

URW (SA)

20 Cardiff Court

Cavan SA 5094

Mobility

No information available. A low mobility would be expected in a landfill setting.

13. DISPOSAL CONSIDERATIONS

Disposal Methods &

Follow safety requirements indicated in Section 6.

Containers

Collect in containers and dispose as trade waste in accordance with local authority

guidelines.

Special considerations for landfill or incineration

Avoid generating dust during disposal..

14. TRANSPORT INFORMATION

UN Number None allocated
UN Proper shipping Name None allocated
Class & Subsidiary Risk Not applicable
Packaging Group None allocated

Special Precautions for Use

Hazchem Code

Avoid generating and breathing dust None allocated

15. REGULATORY INFORMATION

Australian Legislation Hazardous according to criteria of NOHSC...

Poison schedule Not listed

Registration

Australia (AICS) Listed/registered
New Zealand (ERMA) Listed/registered

16. OTHER INFORMATION

Date amended and issued 24th July 2015

Prepared in accordance with the National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition (NOHSC: 2011 (2003))

END OF REPORT



Unitex

22 Park Drive Dandenong VIC 3175

Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au Unitex (NSW)

14 Artisan Road Seven Hills NSW 2147

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

Phone: **1800 RENDER**Fax **(03) 9544 3620 www.render.com.au**

URW (SA) 20 Cardiff Court Cavan SA 5094

Phone: (08) 8262 7900 Fax (08) 8262 7922 www.render.com.au

This information contained herein relates only to the specific material identified. Unitex Granular Marble Pty Ltd believes that such information is accurate and reliable as of the date of this material safety data sheet, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability or completeness of the information.

Unitex urges persons receiving this information to make their own determination as to the information's suitability and completeness for their particular application.