

MATERIAL SAFETY DATA SHEET

PRODUCT: VENETO 826 MINERAL COLOURED FINSHES



Unitex
22 Park Drive
Dandenong Vic 3175
Phone: 03 9768 4900
Fax: 03 9768 4999

Unitex
14 Artisan Road
Seven Hills NSW 2147
Phone: 02 9838 0911
Fax: 02 9838 9555

MATERIAL SAFETY DATA SHEET

PRODUCT: Veneto 826 Mineral Coloured Finishes
(range of exterior wall finishes)

DATE OF ISSUE: 22nd May 2012

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Information

Trade name: Veneto 826 Mineral Coloured Finishes
(range of exterior wall finishes)

Company: Unitex Granular Marble Pty Ltd
22 Park Drive
Dandenong, Vic. 3175
Australia

Telephone: +61 3 9768 4900
Telefax: +61 3 9768 4999

Emergency telephone Number: +61 3 9768 4900 (BH)

Use of the Product: exterior pigmented finish for walls

2. HAZARDS IDENTIFICATION

Classified as hazardous according to the criteria of NOHSC

Not classified as dangerous goods according to the Australian Code for Transport of Dangerous Goods.

This product contains Portland cement which is classified as hazardous.

Risk phrases for Portland cement are:

MATERIAL SAFETY DATA SHEET

PRODUCT: VENETO 826 MINERAL COLOURED FINSHES

R36/37/38 Irritating to eyes, respiratory system and skin
R40 Possible risk of irreversible effects
R43 May cause sensitization by skin contact
R48/20 Harmful: danger of serious damage to health by prolonged exposure
through inhalation

Safety Phrases for Portland cement

S22 Do not breathe dust
S24/25 Avoid contact with skin and eyes
S36/37 Wear suitable protective clothing and gloves

The chemical composition of the product is essentially oxides of various elements, the most prevalent being oxides of calcium Ca, silica Si, aluminium Al, iron Fe, titanium Ti, chromium Cr (mostly as insoluble Cr III but it is possible that water soluble Cr IV could be present at concentrations of less than 10 ppm). Trace amounts of oxides of magnesium Mg, potassium K and phosphorus P may also be present. As cement is a blended product, crystalline silica at levels less than 0.1 % may be present.

Not classified as dangerous goods according to the Australian Code for Transport of Dangerous Goods. NON DANGEROUS GOODS

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS Number	Proportion
Portland cement	65997-15-1	38-48 %
Mineral grains	Proprietary	50-70 %
Inorganic oxide pigments	Proprietary	< 10 %
Functional additives	Proprietary	1-5 %

The chemical composition of the product is essentially oxides of various elements, the most prevalent being oxides of calcium Ca, silicon Si, aluminium Al, chromium Cr (mostly as insoluble non-bioavailable Cr III but it is possible that water soluble bio-available Cr VI could be present at concentrations of less than 10 ppm). Pigment contents vary depending on the shade but involve oxides containing titanium Ti, iron Fe and chromium III (no Cr VI !). Trace amounts of oxides of magnesium Mg, potassium K and phosphorus P may also be present. As cement is a blended product, crystalline silica at levels less than 0.1 % may be present

4. FIRST AID MEASURES

4.1 Health Effects

Swallowed

Health effects Is mildly abrasive and corrosive and may cause nausea/stomach cramps/constipation. Unlikely under normal conditions of use.

MATERIAL SAFETY DATA SHEET

PRODUCT: VENETO 826 MINERAL COLOURED FINSHES

First Aid: Rinse mouth with milk or water. DO NOT give carbonated (fizzy) drinks. DO NOT induce vomiting. After rinsing the mouth, give plenty of water to drink. If symptoms persist, seek medical attention.

Eyes

Health effects Irritating and corrosive to the eyes. May cause chemical conjunctivitis, redness, watering and damage to the cornea.

First Aid: Flush eyes with tepid running water for at least 15 minutes, removing any foreign bodies. Seek medical attention if symptoms persist.

Skin Health effects: Irritating and drying to skin – can result in irritant dermatitis from mechanical abrasion. Wet mortar is irritating and corrosive to skin and may cause skin sensitization (dermatitis). There may be a trace of hexavalent chromium present in Portland cement which may cause allergic dermatitis in some individuals.

First Aid Wash with tepid soapy water; shower if necessary.

Inhaled

Health effects: Irritating to the nose, throat and respiratory tract causing coughing and sneezing. Repeated inhalation of the dust may cause bronchitis.

First Aid: Remove to fresh air. Keep at rest. Seek medical advice if symptoms persist.

4.2 Chronic Health Effects

Repeated inhalation of dust may cause bronchitis. It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs).

Advice to Doctor

Treat symptomatically.

Aggravated Medical Conditions Caused by Exposure

Studies have shown that smoking increases the risk of bronchitis. It is recommended that all storage and work areas should be smoke free zones.

5. FIRE-FIGHTING MEASURES

Hazchem Code	None allocated
Flammability	Not flammable
Extinguishing media	None required
Hazards from combustion products	None – does not decompose on heating
Special Protective Precautions & Equipment for Fire Fighters	None

MATERIAL SAFETY DATA SHEET

PRODUCT: VENETO 826 MINERAL COLOURED FINSHES

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Avoid generating and breathing dust. If dust is generated, wear a class P1 or P2 particulate respirator (AS/NZS 1715, 1716).

Containment Procedures

A fine water spray should be used to suppress dust when sweeping.

Clean-up Procedures

Work areas should be cleaned regularly by wet sweeping or vacuuming. If dust generation cannot be avoided, follow PERSONAL PROTECTION recommendations.

7. HANDLING AND STORAGE

Safe handling advice

Provide good ventilation or extraction.

Wear personal protective equipment.

Veneto 826 Mineral Coloured Finishes are supplied in 20 kg plastic pails. It is recommended that all manual handling of products greater than 15 kg be undertaken by load shifting equipment. Manual handling of this product is not recommended as this may result in personal injury. If no mechanical aids are available, you must not lift this product unless you share the load with 2 or more persons for weights from 15 to 20 kilograms and 3 or more persons up to 40 kilograms. For weights greater than 40 kilograms, mechanical aids for load shifting must be used. Prior to manual handling, it is recommended that a manual handling risk assessment be undertaken.

Use local mechanical ventilation or extraction in areas where dust could escape into the work environment.

Advice on protection against fire and explosion

No special protective measures against fire required.

Storage

Veneto 826 Mineral Coloured Finishes should be stored in a dry place, in the original pails.

Avoid moisture to prevent hardening.

Drivers of trucks transporting Veneto 826 Mineral Coloured Finishes should ensure that the pails are correctly restrained on a pallet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Veneto 826 Mineral Coloured Finishes are supplied as a dry powder. Prior to application, the powder is mixed with water and mixed to a consistent slurry and is then trowel or spray applied onto masonry surfaces such as walls. As Veneto 826 Mineral Coloured Finishes contain Portland cement as a component, and as Portland cement is classed as a Hazardous, Non-Dangerous product, the Precautions for Use of Veneto 826 Mineral Coloured Finishes are the same as for Portland cement.

MATERIAL SAFETY DATA SHEET

PRODUCT: VENETO 826 MINERAL COLOURED FINSHES

Wet Portland cement, particularly in plastic (unhardened) concrete, mortar or slurry, can dry the skin and cause alkali burns. Continued exposure to individuals who are allergic to chromium, could cause severe allergic dermatitis.

For powder Portland cement, keep exposure to dust as low as possible. If inspirable dust levels are kept below 2 mg/m³, health problems such as skin, eye and respiratory irritation will be minimised.

Respirable crystalline silica (quartz) exposure limits should be kept below 0.1 mg/m³ TWA. Avoid repeated skin contact with wet concrete and dry and wet cement.

Engineering Controls

Avoid generating dust. All work with cement should be carried out in such a way as to minimize exposure to dust and repeated skin contact. Where dust could be generated whilst handling cement, use local mechanical ventilation or extraction in areas where dust could escape into the work environment. For bulk deliveries, closed pumping systems are recommended. For handling of individual bags, follow personal protection instructions below if no local exhaust ventilation is available.

Work areas should be cleaned regularly by wet sweeping or vacuuming. If generating dust cannot be avoided, see personal protection recommendations below.

Ventilation

Where practical, suitable means of dust collection/suppression should be applied as necessary to maintain acceptable airborne dust levels.

Persons with a history of respiratory illness or reduced pulmonary function should avoid work places with high dust levels.

Personal Protection

Skin

Wear loose comfortable protective clothing and impervious boots. Apply barrier creams to hands or wear gloves (AS 2161). Wash thoroughly after handling. Wash clothes regularly and keep separate from other clothes.

Eyes

Safety spectacles with side shields or safety goggles (dust resistant AS/NZS 1336) should be worn if dust is likely to be generated.

Respiratory

If dust is generated, wear a class P1 or P2 particulate respirator (AS/NZS 1715 & 1716). Use only respirators which bear the Australian Standards mark and are fitted correctly. Note that persons with facial hair will have difficulty in obtaining a satisfactory face seal. For alternatives, see AS/NZS 1715: Selection and Use of Respiratory Protective Devices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form	Powder
Colour	variety of earthy tones
Odour	nil

Safety data

MATERIAL SAFETY DATA SHEET

PRODUCT: VENETO 826 MINERAL COLOURED FINSHES

Boiling Point/ Melting Point (°C):	Not Applicable
Vapour Pressure:	Not Applicable
% Volatiles:	Not Applicable
Specific Gravity:	approximately 2.5-3.0 g/cm ³
Bulk Density:	0.7 ±0.1 litre/kg
Auto Ignition Temperature:	Not Applicable

10. STABILITY AND REACTIVITY

Chemical Stability	Chemically stable
Conditions to avoid	Keep in moisture proof containers to prevent hardening
Incompatible materials	Will harden in moist conditions
Hazardous Decomposition Products	None
Hazardous Reactions	None with the normal range of industrial materials

11. TOXICOLOGICAL INFORMATION

Health effects from the likely routes of exposure	Refer Section 4: FIRST AID MEASURES
--	-------------------------------------

12. ECOLOGICAL INFORMATION

Ecotoxicity	No information available. Product may be eco-damaging as it can form an alkaline slurry with water
Persistence & Degradability	Product would be persistent and have a low degradability
Mobility	No information available. A low mobility would be expected in a landfill setting

13. DISPOSAL CONSIDERATIONS

Disposal Methods &	Follow safety requirements indicated in Section 6.
-------------------------------	--

MATERIAL SAFETY DATA SHEET

PRODUCT: VENETO 826 MINERAL COLOURED FINSHES

Containers	Collect in containers and dispose as trade waste in accordance with local authority guidelines
Special considerations for landfill or incineration	Avoid generating dust during disposal.

14. TRANSPORT INFORMATION

UN Number	None allocated
UN Proper shipping Name	None allocated
Class & Subsidiary Risk	Not applicable
Packaging Group	None allocated
Special Precautions for Use	Avoid generating and breathing dust
Hazchem Code	None allocated

15. REGULATORY INFORMATION

Australian Legislation	Hazardous according to criteria of NOHSC
Poison schedule	Not listed
Registration	
Australia (AICS)	Listed/registered
New Zealand (ERMA)	Listed/registered

16. OTHER INFORMATION

Date amended and issued; 22nd May 2012

Prepared in accordance with the National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition (NOHSC: 2011 (2003))

END OF REPORT

MATERIAL SAFETY DATA SHEET

PRODUCT: VENETO 826 MINERAL COLOURED FINSHES



D +61 (0) 3 9768 4900
F +61 (0) 3 9768 4999

22 Park Drive
Dandenong VIC 3175

Free plan pick-up
Quote service
www.unitex.com.au

This information contained herein relates only to the specific material identified. Unitex Granular Marble Pty Ltd believes that such information is accurate and reliable as of the date of this material safety data sheet, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability or completeness of the information.

Unitex urges persons receiving this information to make their own determination as to the information's suitability and completeness for their particular application.