

Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au

Unitex (NSW) 14 Artisan Road Seven Hills NSW 2147

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au

URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

Phone: 1800 RENDER Phone: (08) 8262 7900 Fax (03) 9544 3620 Fax (08) 8262 7922 www.render.com.au www.render.com.au

URW (SA)

20 Cardiff Court

Cavan SA 5094

Safety Data Sheet

Hazardous Substance, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product Information

Trade name: Unitex® Panel Patch

Company Unitex Granular Marble Pty Ltd

22 Park Drive

Dandenong, Vic. 3175

Australia

Telephone +61 3 9768 4900 **Telefax** +61 3 9768 4999

Emergency telephone

number

+61 3 9768 4900 (BH)

Use of the Product patching compound with 4-hour fire rating. Applied by trowel.

2. HAZARDS IDENTIFICATION

This material is hazardous according to the health criteria of Safe Work Australia

Signal Word

Danger

Hazard Classification

Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Irritation - Category 1

Specific Target Organ Toxicity (Single Exposure) - Category 3

Prevention Precautionary Statement(s)

P102 Keep out of reach of children P103 Read label before use P261 Avoid breathing dust

Wash hands, face and all exposed skin thoroughly after handling P264

P271 Use only outdoors or in a well ventilated area.

Wear protective clothing, gloves, eye/face protection and suitable dust mask P280



Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au Unitex (NSW)

14 Artisan Road

Seven Hills NSW 2147

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au **URW (Oakleigh)** 1346 North Road Oakleigh VIC 3167 URW (SA) 20 Cardiff Court Cavan SA 5094

Phone: 1800 RENDER Phone: (08) 8262 7900
Fax (03) 9544 3620 Fax (08) 8262 7922
www.render.com.au www.render.com.au

Response Precautionary Statement(s)

P101 If medical advice is needed, have product container or label at hand P312 Call a POISON CENTRE or doctor/physician if you feel unwell

P302+352 IF ON SKIN: Wash with soap and water

P362 Take off contaminated clothing and wash before reuse P332+313 If skin irritation occurs: Get medical advice/attention

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P314 Get medical advice/attention if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do –

continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician

Storage Precautionary Statement(s)

P405 Store locked up

P403+233 Store in a well ventilated place. Keep container tightly closed

Disposal Precautionary Statement(s)

P501 Dispose of contents/container in accordance with local, regional, national and international regulations

Poisons Schedule (Aust): Not applicable

DANGEROUS GOODS CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail".

3. COMPOSITION / INFORMATION ON INGREDIENTS

IngredientsCAS NumberProportionPortland cement65997-15-140-50 %Crystalline silica, respirable14808-60-7< 0.1 %</td>Ingredients determined to be non-hazardousBalance

Panel Patch does not contain any Red List chemicals. The Red List chemicals are:

- Alkylphenols
- Asbestos
- Bisphenol A (BPA)
- Cadmium
- Chlorinated Polyethylene and Chlorosulphonated Polyethylene
- Chlorobenzenes
- Chlorofluorocarbons (CFCs) and Hydrochlorofluorocarbons (HCFCs)
- Chloroprene (Neoprene)
- Chromium VI
- Chlorinated Polyvinyl Chloride (CPVC)
- Formaldehyde (added)
- Halogenated Flame Retardants (HFRs)
- Lead (added)
- Mercury
- Polychlorinated Biphenyls (PCBs)
- Perfluorinated Compounds (PFCs)
- Phthalates
- Polyvinyl Chloride (PVC)
- Polyvinylidene Chloride (PVDC)
- Short Chain Chlorinated Paraffins



Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au Unitex (NSW)

14 Artisan Road

Seven Hills NSW 2147

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

20 Cardiff Court Cavan SA 5094

URW (SA)

Phone: 1800 RENDER Phone: (08) 8262 7900
Fax (03) 9544 3620 Fax (08) 8262 7922
www.render.com.au www.render.com.au

- Wood treatments containing Creosote, Arsenic or Pentachlorophenol
- Volatile Organic Compounds (VOCs) in wet-applied products

4. FIRST AID MEASURES

4.1 Health Effects

Swallowed

Health effects Is mildly abrasive and corrosive and may cause nausea/stomach cramps/constipation. Unlikely under normal conditions of use.

First Aid: Rinse mouth with milk or water. DO NOT give carbonated (fizzy) drinks. DO NOT induce vomiting. After rinsing the mouth, give plenty of water to drink. If symptoms persist, seek medical attention.

Eyes

Health effects Irritating and corrosive to the eyes. May cause chemical conjunctivitis, redness, watering and damage to the cornea.

First Aid: Flush eyes with tepid running water for at least 15 minutes, removing any foreign bodies. Seek medical attention if symptoms persist.

Skin Health effects: Irritating and drying to skin – can result in irritant dermatitis from mechanical abrasion. Wet render is irritating and corrosive to skin and may cause skin sensitization (dermatitis). There may be a trace of hexavalent chromium present in Portland cement which may cause allergic dermatitis in some individuals.

First Aid Wash with tepid soapy water; shower if necessary.

Inhaled

Health effects: Irritating to the nose, throat and respiratory tract causing coughing and sneezing. Repeated inhalation of the dust may cause bronchitis.

First Aid: Remove to fresh air. Keep at rest. Seek medical advice if symptoms persist.

4.2 Chronic Health Effects

Repeated inhalation of dust may cause bronchitis. It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs).

Advice to Doctor

Treat symptomatically.

Aggravated Medical Conditions Caused by Exposure

Studies have shown that smoking increases the risk of bronchitis. It is recommended that all storage and work areas should be smoke free zones.

5. FIRE-FIGHTING MEASURES

Hazchem CodeNone allocatedFlammabilityNot flammableExtinguishing mediaNone required

Hazards from combustion products

None – does not decompose on heating

MATERIAL SAFETY DATA SHEET



Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au Unitex (NSW)
14 Artisan Road
Seven Hills NSW 2147

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

Phone: 1800 RENDER
Fax (03) 9544 3620
www.render.com.au

URW (SA) 20 Cardiff Court Cavan SA 5094

Phone: (08) 8262 7900 Fax (08) 8262 7922 www.render.com.au

Special Protective Precautions & Equipment for Fire Fighters

None

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Avoid generating and breathing dust. If dust is generated, wear a class P1 or P2 particulate respirator (AS/NZS 1715, 1716).

Containment Procedures

A fine water spray should be used to suppress dust when sweeping.

Clean-up Procedures

Work areas should be cleaned regularly by wet sweeping or vacuuming. If dust generation cannot be avoided, follow PERSONAL PROTECTION recommendations.

7. HANDLING AND STORAGE

Safe handling advice

Provide good ventilation or extraction.

Wear personal protective equipment.

Unitex® Panel Patch is packed in 8 kg multi-ply valve pack paper sacks. There are no special provisions for lifting these sacks.

Use local mechanical ventilation or extraction in areas where dust could escape into the work environment.

Personal safety requirements are outlined in Section: Exposure Control / Personal Protection.

Advice on protection against fire and explosion

No special protective measures against fire required.

Storage

Unitex® Panel Patch should be stored in a dry place, in the original multi ply paper sacks. Avoid moisture to prevent hardening.

Drivers of trucks transporting Unitex® Panel Patch should ensure that the paper sacks are correctly restrained on a pallet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure Limits

Unitex® Panel Patch is supplied as a blended dry powder. Prior to application, the powder is mixed with water with a mechanical stirrer to a smooth consistency and is then troweled onto moulded cement profiles and other building products such as lightweight concrete block-work and panels. As Unitex® Panel Patch contains Portland cement as a major component, it is classed as a Hazardous, Non-Dangerous product.,

For the blended, dry .powder, the National Exposure Standard from Worksafe Australia is:



Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au Unitex (NSW) 14 Artisan Road Seven Hills NSW 2147

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

Phone: 1800 RENDER
Fax (03) 9544 3620
www.render.com.au

20 Cardiff Court Cavan SA 5094

URW (SA)

Phone: (08) 8262 7900 Fax (08) 8262 7922 www.render.com.au

Total dust, containing no asbestos and < 1 % crystalline silica, Threshold Limit Value (TLV) Time Weighted Average (TWA) 10 mg/m³ measured as respirable dust.

Crystalline silica (quartz): 0.2 mg/m³ TWA as respirable dust (< 7 micron particle equivalent aerodynamic diameter).

Respirable crystalline silica (quartz) exposure levels should be kept below a recommended upper threshold limit of 0.05 mg/m³ TWA.

However, where a State or Territory prescribes a lower exposure standard, the lower exposure standard applies. When wet, Unitex® Panel Patch, particularly in slurry form, can dry the skin and cause alkali burns. Continued exposure to individuals who are allergic to chromium, could cause severe allergic dermatitis.

For powder Portland cement, keep exposure to dust as low as possible. If inspirable dust levels are kept below 2 mg/m³, health problems such as skin, eye and respiratory irritation will be minimised.

8.2 Engineering Controls

Avoid generating dust. All work with Unitex® Panel Patch should be carried out in such a way as to minimize exposure to dust and repeated skin contact. Where dust could be generated whilst handling the product, use local mechanical ventilation or extraction in areas where dust could escape into the work environment.

Work areas should be cleaned regularly by wet sweeping or vacuuming. If generating dust cannot be avoided, see personal protection recommendations below.

8.3 Ventilation

Where practical, the workplace should be well ventilated with suitable means of dust collection/suppression equipment so as to maintain acceptable airborne dust levels.

Persons with a history of respiratory illness or reduced pulmonary function should avoid work places with high dust levels.

8.4 Personal Protection

Skin

Wear loose comfortable protective clothing and impervious boots. Apply barrier creams to hands or wear cotton or light duty leather gloves (ASNZS 2161). Wash thoroughly after handling. Wash clothes regularly and keep separate from other clothes.

Eyes

Safety spectacles with side shields or safety goggles (dust resistant AS/NZS 1336) should be worn if dust is likely to be generated.

Respiratory

If dust is generated, wear a class P1 or P2 particulate respirator (AS/NZS 1715). Use only respirators which bear the Australian Standards mark and are fitted correctly. Note that persons with facial hair will have difficulty in obtaining a satisfactory face seal. For alternatives, see AS/NZS 1715: Selection and maintenance of Respiratory Protective Devices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form Powder

Colour Off-White to Grey



Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au Unitex (NSW)
14 Artisan Road
Seven Hills NSW 2147

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

Phone: 1800 RENDER Phone
Fax (03) 9544 3620 Fax
www.render.com.au www

URW (SA) 20 Cardiff Court Cavan SA 5094

Phone: (08) 8262 7900
Fax (08) 8262 7922
www.render.com.au

Odour nil

pH alkaline slurry formed with water

Density approx $1.3 - 1.8 \text{ g/cm}^3$

Boiling point not applicable

Freezing/Melting point > 1400 °C

Vapour density not applicable

Vapour pressure not applicable

Solubility essentially insoluble, however, some components

are slightly soluble in water forming an alkaline

(caustic) product

Flash point not applicable

Ignition temperature not applicable

Additional Information Respirable Fraction: approx 5-10 % of particles are

below 7 microns in diameter (in the respirable range)

10. STABILITY AND REACTIVITY

Chemical Stability Chemically stable

Conditions to avoid Keep in moisture proof containers to prevent hardening.

Incompatible Materials Will harden in moist conditions.

Hazardous Decomposition

Products

None

Hazardous Reactions Avoid reaction with hydrogen fluoride (hydrofluoric

acid) and other fluorine containing compounds

11. TOXICOLOGICAL INFORMATION

Health effects from the likely

routes of exposure

Refer Section 4: FIRST AID MEASURES

12. ECOLOGICAL INFORMATION

Ecotoxicity No information available. Product may be eco-



Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au Unitex (NSW)
14 Artisan Road
Seven Hills NSW 2147

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au URW (Oakleigh) 1346 North Road Oakleigh VIC 3167

Phone: 1800 RENDER Phoner: 1800 RENDER Phoner:

URW (SA) 20 Cardiff Court Cavan SA 5094

Phone: (08) 8262 7900
Fax (08) 8262 7922
www.render.com.au

damaging as it can form an alkaline slurry with water

Persistence & Degradability Product would be persistent and have a low

degradability

Mobility No information available. A low mobility would be

expected in a landfill setting

13. DISPOSAL CONSIDERATIONS

Disposal Methods &

landfill or incineration

Containers

Follow safety requirements indicated in Section 6. Collect in containers and dispose as trade waste in accordance with local authority guidelines

Special considerations for

Avoid generating dust during disposal.

14. TRANSPORT INFORMATION

UN Number UN Proper shipping Name Class & Subsidiary Risk Packaging Group

Special Precautions for Use

Hazchem Code

None allocated None allocated Not applicable None allocated

Avoid generating and breathing dust

None allocated

15. REGULATORY INFORMATION

Australian Legislation Hazardous according to criteria of Safe Work Australia

Poison schedule Not listed

Registration

Australia (AICS) Listed/registered New Zealand (ERMA) Listed/registered

16. OTHER INFORMATION

Date amended and issued; 8th November 2018

Prepared in accordance with the National model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals (2011)

END OF REPORT



Phone: (03) 9768 4900 Fax (03) 9768 4999 www.unitex.com.au Unitex (NSW) 14 Artisan Road Seven Hills NSW 2147

Phone: (02) 9838 0911 Fax (02) 9838 9555 www.unitex.com.au **URW (Oakleigh)** 1346 North Road Oakleigh VIC 3167

Phone: 1800 RENDER Fax (03) 9544 3620 www.render.com.au URW (SA) 20 Cardiff Court Cavan SA 5094

Phone: (08) 8262 7900 Fax (08) 8262 7922 www.render.com.au

This information contained herein relates only to the specific material identified. Unitex Granular Marble Pty Ltd believes that such information is accurate and reliable as of the date of this safety data sheet, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability or completeness of the information.

Unitex urges persons receiving this information to make their own determination as to the information's suitability and completeness for their particular application.